



01773 620111

**PIRTEK**  
fluid transfer solutions



Mobile hose replacement - ETA 1 hr

PIRTEK  
ETA 1 hr

2018 Ford Transit  
2.0 EcoBlue 162CV














L9571-01

3.1	<i>Rubber Hose</i>	345
3.2	<i>PVC Hose</i>	353
3.3	<i>Ducting Hose</i>	359
3.4	<i>Conduit</i>	365
3.5	<i>Metallic Hose Assembiles</i>	371
3.6	<i>Composite Hose Assembiles</i>	377
3.7	<i>Hygienic Hose &amp; Couplings</i>	381
3.8	<i>Fire Hose &amp; Couplings</i>	391
3.9	<i>Suction &amp; Delivery Couplings</i>	395
3.10	<i>Cam &amp; Groove Couplings</i>	407
3.11	<i>Tanker Truck Couplings</i>	415
3.12	<i>Brass and S.Steel Hose Couplings</i>	423
3.13	<i>Stainless Steel Pipe Couplings</i>	431
3.14	<i>Nylon Hose Couplings</i>	437
3.15	<i>Hose Clips &amp; Clamps</i>	441



### PRODUCT INDEX

The Pirtek industrial hose range will cater for most common mediums and is designed to complement the hydraulic hose range.

	Series	Page		Series	Page		
	Air and Water Hose	IPNBL25	346		Chemical Suction and Delivery Hose	IPXL10	350
	Air Delivery Hose	IMIN10	346		Fuel Hose	TBE	350
	Anti-Static Air Hose	ITUR20	346		Fuel Hose	TBSE	350
	Air Delivery Hose	IAIR20	346		Marine Fuel Hose	TBDE	350
	Air Brake Hose	J1402	346		Car Heater Hose SAE 20R3 c (212)	ICAR	350
	Compressor Hose	ICOM20	347		Fuel Hose Dispenser	FHD	351
	Compressor Hose Assembly	COMP	347				
	Suction and Delivery Food Grade Hose	IGAM10	347				
	Delivery Food Grade Hose	IDRI10	347		Swage Ferrule for Industrial and PVC Hose - Light Duty Steel	LDF	351
	Welding Hose	IWNB-20	347		Swage Ferrule for Industrial and PVC Hose - Light Duty Brass	BR/LDF	351
	Twin Line Welding Hose	IWBI20	347		Swage Ferrule for Industrial and PVC Hose - Light Duty Aluminium	AL/LDF	351
	Propane Gas Hose	IPRO20	347		Swage Ferrule for Industrial and PVC Hose - Light Duty Stainless Steel	SS/LDF	352
	Steam Hose Red	IVIG17	348		Propane Gas Hose EN559/BS3212	GS/IPRO20	352
	Steam Hose Black	IVIG17B	348		Propane Gas Hose EN559/BS3212	WR/IPRO20	352
	Water Suction and Delivery Hose	IBEV10	348		Fuel Hose Stainless Steel Overbraided	SS/PVZA	352
	Water Suction and Delivery Hose	IWSH10	348		Fuel Hose Galvanised Steel Overbraided	GS PVZA	352
	Radiator Hose	IRAD	349				
	Silicone Radiator Hose	SIL	349				
	Silicone Radiator Hose	SIL90	349				
	Oil Delivery Hose	100R6	349				
	Oil Suction and Delivery Hose	100S4	350				

For Technical Data please see Section 9

### Air and Water Hose - IPNBL25



**Tube:** Black, smooth SBR rubber.  
**Reinforcement:** Synthetic textile yarns.  
**Cover:** Blue, abrasion, ageing and weather resistant SBR/EPDM rubber.  
**Coil Lengths:** 30 up to 100 metres.  
**Temperature Range:** -20°C to + 70°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IPNBL25-006</b>	1/4	6	14	362	25
<b>IPNBL25-010</b>	3/8	10	19	362	25
<b>IPNBL25-013</b>	1/2	13	24	362	25
<b>IPNBL25-019</b>	3/4	19	32	362	25
<b>IPNBL25-025</b>	1	25	39	362	25

### Air Delivery Hose - BS EN ISO 2398/BS 5118/2 -IAIR20



**Tube:** Black, smooth synthetic rubber.  
**Reinforcement:** Synthetic textile yarns.  
**Cover:** Black, smooth SBR/EPDM rubber, resistant to abrasion, ageing and weathering.  
**Coil Lengths:** 50 up to 100 metres.  
**Temperature Range:** -20°C to + 80°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IAIR20-006</b>	1/4	6.5	14	290	20
<b>IAIR20-008</b>	5/16	8	16	290	20
<b>IAIR20-010</b>	3/8	9.5	18	290	20
<b>IAIR20-013</b>	1/2	12.7	23	290	20
<b>IAIR20-019</b>	3/4	19	30	290	20
<b>IAIR20-025</b>	1	25	37	290	20

### Air Delivery Hose - IMIN10



**Tube:** Black, oil, mist resistant smooth SBR rubber.  
**Reinforcement:** Synthetic textile fabrics.  
**Cover:** Black, abrasion, ageing and weather resistant SBR rubber.  
**Coil Lengths:** 40 metres.  
**Temperature Range:** -30°C to + 70°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IMIN10-032</b>	1 1/4	32	42	145	10
<b>IMIN10-038</b>	1 1/2	38	48	145	10
<b>IMIN10-050</b>	2	50	60	145	10

### Air Delivery Hose - SAE J1402-A



**Tube:** Black, smooth NBR rubber.  
**Reinforcement:** Synthetic textile yarns.  
**Cover:** Black, smooth, abrasion, ageing and weather-resistant CR rubber.  
**Coil Lengths:** 50 metres.  
**Temperature Range:** -40°C to + 93°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>J1402-04</b>	1/4	6.3	15.9	145	10
<b>J1402-05</b>	5/16	7.9	17.5	145	10
<b>J1402-06</b>	3/8	9.5	19.5	145	10
<b>J1402-08</b>	1/2	12.7	22.2	145	10
<b>J1402-10</b>	5/8	15.9	27	145	10

### Anti-Static Air Hose - BS EN ISO 2398/BS 5118/2 -ITUR20



**Tube:** Black, resistant to traces of oil mist, antistatic, smooth EPDM rubber.  
**Reinforcement:** Synthetic textile yarns.  
**Cover:** Black, abrasion and weather resistant, antistatic EPDM rubber.  
**Coil Lengths:** 30 up to 100 metres.  
**Temperature Range:** -30°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>ITUR20-010</b>	3/8	10	19	290	20
<b>ITUR20-013</b>	1/2	13	23	290	20
<b>ITUR20-019</b>	3/4	19	30	290	20
<b>ITUR20-025</b>	1	25	37	290	20

### Compressor Hose - BS EN ISO 2398/BS 5118/2 -ICOM20



**Tube:** Black, resistant to minimum oil traces, smooth SBR rubber.  
**Reinforcement:** Synthetic textile fabrics.  
**Cover:** Yellow, abrasion and weather resistant SBR rubber.  
**Coil Lengths:** 20 up to 40 metres.  
**Temperature Range:** -30°C to + 70°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>ICOM20-019</b>	3/4	19	30	290	20
<b>ICOM20-025</b>	1	25	36	290	20
<b>ICOM20-032</b>	1 1/4	32	48	290	20
<b>ICOM20-038</b>	1 1/2	38	51	290	20
<b>ICOM20-051</b>	2	51	66	290	20

### Compressor Hose Assembly - BS 5118/2 - COMP

**Tube:** Black, Rubber  
**Reinforcement:** Synthetic textile fabrics.  
**Cover:** Yellow, abrasion and weather resistant Rubl  
**Coil Lengths:** 15 metres.  
**Temperature Range:** -25°C to + 70°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>*COMP-05</b>	3/4	19	30	290	20

\*(Complete with safety clamps)



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>**COMP-06</b>	3/4	19	30	232	16

\*\* (Complete with crimped fittings)

### Suction and Delivery Food Grade Hose - IGAM10

**Tube:** Rubber hose with smooth, white, food quality inner tube.  
**Reinforcement:** Textile yarn and embedded metal spiral reinforcement.  
**Cover:** Blue, abrasion, ageing and weather resistant.  
**Coil Lengths:** 40 metres.  
**Temperature Range:** -40°C to + 90°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IGAM10-025</b>	1	25	37	145	10
<b>IGAM10-032</b>	1 1/4	32	44	145	10
<b>IGAM10-038</b>	1 1/2	38	50	145	10
<b>IGAM10-050</b>	2	51	65	145	10
<b>IGAM10-063</b>	2 1/2	63.5	77	145	10

### Delivery Food Grade Hose - IDRI10

**Tube:** White colour, non-toxic, smooth synthetic rubber.  
**Reinforcement:** Synthetic textile yarns.  
**Cover:** Blue smooth, abrasion, and weather resistant synthetic rubber.  
**Coil Lengths:** 30 up to 100 metres.  
**Temperature Range:** -15°C to + 70°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IDRI10-010</b>	3/8	10	19	145	10
<b>IDRI10-013</b>	1/2	13	23	145	10
<b>IDRI10-016</b>	5/8	16	26	145	10
<b>IDRI10-019</b>	3/4	19	31	145	10
<b>IDRI10-025</b>	1	25	39	145	10

### Welding Hose EN559 - IWNB20 - Blue IWNR20 - Red

**Tube:** Black, smooth SBR rubber, resistant to welding gases. (Not suitable for LPG). Good resistance to ignition.  
**Reinforcement:** Synthetic textile yarns.  
**Cover:** Smooth, Blue or Red SBR/EPDM rubber, resistant to abrasion, ageing, hot surfaces and incandescent particles.  
**Coil Lengths:** 30 up to 100 metres.  
**Temperature Range:** -25°C to + 80°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IWNB20-006</b>	1/4	6	12	290	20
<b>IWNB20-010</b>	3/8	10	17	290	20
<b>IWNR20-006</b>	1/4	6	12	290	20
<b>IWNR20-010</b>	3/8	10	17	290	20

### Twin-Line Welding Hose EN559 - IWB120

**Tube:** Black, smooth SBR rubber, resistant to welding gases. (Not suitable for LPG). Good resistance to ignition.  
**Reinforcement:** Synthetic textile yarns.  
**Cover:** Dual Blue and Red smooth SBR/EPDM rubber, resistant to abrasion, ageing, hot surfaces and incandescent particles.  
**Coil Lengths:** 30 up to 100 metres.  
**Temperature Range:** -25°C to + 80°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IWB120-006</b>	1/4	6	12	290	20
<b>IWB120-010</b>	3/8	10	17	290	20

### Propane Gas Hose - EN559/BS3212 - IPRO20

**Tube:** Black, LPG-resistant, smooth NBR rubber.  
**Reinforcement:** High strength polyester yarn 2 ply.  
**Cover:** Weather abrasion ozone and flame resistant, orange compound.  
**Coil Lengths:** 30 up to 100 metres.  
**Temperature Range:** -35°C to + 80°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IPRO20-005</b>	3/16	5	12	290	20
<b>IPRO20-006</b>	1/4	6.3	13.3	290	20
<b>IPRO20-008</b>	5/16	8	15	290	20
<b>IPRO20-010</b>	3/8	10	17	290	20
<b>IPRO20-013</b>	1/2	12.5	21	290	20

### Steam Hose Red - IVIG17



**Tube:** Black inner made of heat resistant compounds.  
**Reinforcement:** Metal reinforcement and micro pin pricked.  
**Cover:** Red cloth impression, ageing and weather resistant rubber cover.  
**Coil Lengths:** Up to 61 metres.  
**Temperature Range:** -40°C to + 210°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IVIG17-013</b>	1/2	13	25	250	17
<b>IVIG17-019</b>	3/4	19	32	250	17
<b>IVIG17-025</b>	1	25	38	250	17
<b>IVIG17-038</b>	1 1/2	38	54	250	17

### Steam Hose Black - IVIG17B



**Tube:** Black inner made of heat resistant compounds.  
**Reinforcement:** Metal reinforcement and micro pin pricked.  
**Cover:** Black cloth impression, ageing and weather resistant rubber cover.  
**Coil Lengths:** Up to 61 metres.  
**Temperature Range:** -40°C to + 210°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IVIG17B-013</b>	1/2	13	25	250	17
<b>IVIG17B-019</b>	3/4	19	32	250	17
<b>IVIG17B-025</b>	1	25	38	250	17
<b>IVIG17B-038</b>	1 1/2	38	54	250	17

### Water Suction and Delivery Hose - IBEV10



**Tube:** Black, smooth SBR rubber.  
**Reinforcement:** Synthetic textile fabrics and embedded steel wire helix.  
**Cover:** Black, abrasion, ageing and weather resistant SBR rubber.  
**Coil Lengths:** 61 metres.  
**Temperature Range:** -40°C to +90°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IBEV10-025</b>	1	25	35	145	10
<b>IBEV10-032</b>	1 1/4	32	42	145	10
<b>IBEV10-038</b>	1 1/2	38	49	145	10
<b>IBEV10-050</b>	2	51	62	145	10
<b>IBEV10-063</b>	2 1/2	63.5	76	145	10

### Water Suction and Delivery Hose - IWSH10



**Tube:** Black, smooth EPDM rubber.  
**Reinforcement:** Spiral high tensile cords and four steel helix wires.  
**Cover:** Black weather resistant EPDM rubber.  
**Coil Lengths:** 61 metres.  
**Temperature Range:** -22°C to +90°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IWSH10-019</b>	3/4	19	29	150	10
<b>IWSH10-025</b>	1	25	35	150	10
<b>IWSH10-032</b>	1 1/4	32	42	150	10
<b>IWSH10-038</b>	1 1/2	38	49	150	10
<b>IWSH10-051</b>	2	51	63	150	10
<b>IWSH10-063</b>	2 1/2	63	76	150	10
<b>IWSH10-076</b>	3	76	89	150	10
<b>IWSH10-102</b>	4	102	118	150	10
<b>IWSH10-127</b>	5	127	145	150	10
<b>IWSH10-152</b>	6	152	174	150	10
<b>IWSH10-203</b>	8	203	228	150	10

3-1

### Radiator Hose - IRAD

**Tube:** Black, heat resistant EPDM rubber.  
**Reinforcement:** Synthetic textile fabric with steel wire helix embedded between the layers.  
**Cover:** Black, heat, weather, ozone resistant EPDM rubber.  
**Coil Lengths:** 1 metre.  
**Temperature Range:** -40°C to + 120°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IRAD-14</b>	7/8	22	30	145	10
<b>IRAD-16</b>	1	25	34	145	10
<b>IRAD-18</b>	1 1/8	28	36	145	10
<b>IRAD-20</b>	1 1/4	32	41	145	10
<b>IRAD-22</b>	1 3/8	35	45	145	10
<b>IRAD-24</b>	1 1/2	38	47	145	10
<b>IRAD-28</b>	1 3/4	44.5	55	145	10
<b>IRAD-32</b>	2	51	61	145	10

### Silicone Radiator Hose - SIL

**Tube:** Blue silicone tube resistant to trace oil mist and anti freeze solutions.  
**Reinforcement:** Three ply synthetic textile reinforcements.  
**Cover:** Blue silicone tube resistant to abrasion, aging, weathering, oil mist and anti freeze solutions.  
**Coil Lengths:** 1 metre.  
**Temperature Range:** -50°C to + 235°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>SIL-006</b>	1/4	6	14	25	2
<b>SIL-008</b>	5/16	8	16	25	2
<b>SIL-010</b>	3/8	10	18	25	2
<b>SIL-013</b>	1/2	13	21	25	2
<b>SIL-016</b>	5/8	16	24	25	2
<b>SIL-019</b>	3/4	19	27	25	2
<b>SIL-022</b>	7/8	22	30	25	2
<b>SIL-025</b>	1	25	34	25	2
<b>SIL-028</b>	1 1/8	28	37	25	2
<b>SIL-032</b>	1 1/4	32	41	25	2
<b>SIL-035</b>	1 3/8	35	44	25	2
<b>SIL-038</b>	1 1/2	38	47	25	2
<b>SIL-042</b>	1 5/8	42	50	25	2
<b>SIL-045</b>	1 3/4	45	54	25	2
<b>SIL-048</b>	1 7/8	48	57	25	2
<b>SIL-051</b>	2	51	60	25	2
<b>SIL-054</b>	2 1/8	54	63	25	2
<b>SIL-057</b>	2 1/4	57	67	25	2
<b>SIL-061</b>	2 3/8	61	71	25	2
<b>SIL-063</b>	2 1/2	63	73	25	2
<b>SIL-070</b>	2 3/4	70	80	25	2
<b>SIL-076</b>	3	76	86	25	2
<b>SIL-080</b>	3 1/8	80	90	25	2
<b>SIL-090</b>	3 1/2	90	100	25	2
<b>SIL-102</b>	4	102	112	25	2

### Silicone Radiator Hose - SIL 90

**Tube:** Blue silicone tube resistant to trace oil mist and anti freeze solutions.  
**Reinforcement:** Three ply synthetic textile reinforcements.  
**Cover:** Blue silicone tube resistant to abrasion, aging, weathering, oil mist and anti freeze solutions.  
**Leg Length:** 102 mm.  
**Temperature Range:** -50°C to + 235°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>SIL90-006</b>	1/4	6	14	25	2
<b>SIL90-008</b>	5/16	8	16	25	2
<b>SIL90-010</b>	3/8	10	18	25	2
<b>SIL90-013</b>	1/2	13	21	25	2
<b>SIL90-016</b>	5/8	16	24	25	2
<b>SIL90-019</b>	3/4	19	27	25	2
<b>SIL90-022</b>	7/8	22	30	25	2
<b>SIL90-025</b>	1	25	34	25	2
<b>SIL90-028</b>	1 1/8	28	37	25	2
<b>SIL90-032</b>	1 1/4	32	41	25	2
<b>SIL90-035</b>	1 3/8	35	44	25	2
<b>SIL90-038</b>	1 1/2	38	47	25	2
<b>SIL90-042</b>	1 5/8	42	50	25	2
<b>SIL90-045</b>	1 3/4	45	54	25	2
<b>SIL90-048</b>	1 7/8	48	57	25	2
<b>SIL90-051</b>	2	51	60	25	2
<b>SIL90-054</b>	2 1/8	54	63	25	2
<b>SIL90-057</b>	2 1/4	57	67	25	2
<b>SIL90-061</b>	2 3/8	61	71	25	2
<b>SIL90-063</b>	2 1/2	63	73	25	2
<b>SIL90-070</b>	2 3/4	70	80	25	2
<b>SIL90-076</b>	3	76	86	25	2
<b>SIL90-080</b>	3 1/8	80	90	25	2
<b>SIL90-090</b>	3 1/2	90	100	25	2
<b>SIL90-102</b>	4	102	112	25	2

### Oil Delivery Hose - EN 854 - 100R6

**Tube:** Black, oil resistant NBR rubber.  
**Reinforcement:** Synthetic textile fabrics.  
**Cover:** Black, oil and ozone resistant CR rubber.  
**Coil Lengths:** Up to 50 metres.  
**Temperature Range:** -40°C to + 100°C.



Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>100R6-03</b>	3/16	4.8	11.1	493	34
<b>100R6-04</b>	1/4	6.4	12.7	406	28
<b>100R6-05</b>	5/16	7.9	14.3	406	28
<b>100R6-06</b>	3/8	9.5	15.9	406	28
<b>100R6-08</b>	1/2	12.7	19.8	406	28
<b>100R6-10</b>	5/8	16	23	348	24
<b>100R6-12</b>	3/4	19	27	304	21
<b>100R6-16</b>	1	25	35	290	20

### Oil Suction and Delivery Hose - 100S4



**Tube:** Black, smooth NBR rubber.  
**Reinforcement:** Textile yarn and embedded metal spiral reinforcement, copper wire to ensure the electric conductivity, antistatic smooth, cloth impression.  
**Cover:** Black, oil, abrasion and weathering resistant rubber.  
**Coil Lengths:** 61 metres.  
**Temperature Range:** -40°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>100S4-12</b>	3/4	19	29	145	10
<b>100S4-16</b>	1	25	35	145	10
<b>100S4-20</b>	1 1/4	32	43	145	10
<b>100S4-24</b>	1 1/2	38	50	145	10
<b>100S4-28</b>	1 25/32	45	57	145	10
<b>100S4-32</b>	2	51	63	145	10
<b>100S4-36</b>	2 1/4	57	68	145	10
<b>100S4-38</b>	2 3/8	60	73	145	10
<b>100S4-40</b>	2 1/2	63.5	77	145	10
<b>100S4-48</b>	3	76	90	145	10
<b>100S4-64</b>	4	102	119	145	10

### Chemical Suction and Delivery Hose - IPXL10



**Tube:** Smooth transparent UHMWPE conductive tube.  
**Reinforcement:** Synthetic textile fabrics and embedded steel wire helix.  
**Cover:** Green, cloth impression, abrasion, ozone and weathering resistant rubber.  
**Coil Lengths:** 40 metres.  
**Temperature Range:** -30°C to + 80°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>IPXL10-025</b>	1	25	39	145	10
<b>IPXL10-032</b>	1 1/4	32	46	145	10
<b>IPXL10-038</b>	1 1/2	38	52	145	10
<b>IPXL10-051</b>	2	51	66	145	10

### Fuel Hose BS AU 108 C4/L4/R - TBE



**Tube:** Black smooth rubber suitable for use with diesel, petrol and unleaded fuels.  
**Reinforcement:** Synthetic textile fabric braid.  
**Cover:** Black abrasion resistant rubber bonded with a textile fabric cover.  
**Coil Lengths:** 15 metres.  
**Temperature Range:** -30°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>TBE-003</b>	1/8	3	7	120	8
<b>TBE-004</b>	5/32	4	9	120	8
<b>TBE-005</b>	3/16	5	11	120	8
<b>TBE-006</b>	1/4	6	13	120	8
<b>TBE-008</b>	5/16	8	14.5	120	8

### Fuel Hose BS AU 108 C4/L4/R - TBSE



**Tube:** Black smooth rubber suitable for use with diesel, petrol and unleaded fuels.  
**Reinforcement:** Synthetic textile fabric braid.  
**Cover:** Black smooth abrasion resistant rubber.  
**Coil Lengths:** 15 metres.  
**Temperature Range:** -30°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure	
	ins	mm		PSI	Bar
<b>TBSE-003</b>	1/8	3	7	120	8
<b>TBSE-004</b>	5/32	4	9	120	8
<b>TBSE-005</b>	3/16	5	10	120	8
<b>TBSE-006</b>	1/4	6	13	120	8
<b>TBSE-008</b>	5/16	8	16	120	8
<b>TBSE-010</b>	3/8	10	18	120	8
<b>TBSE-012</b>	1/2	12	23	120	8
<b>TBSE-019</b>	3/4	19	29	120	8
<b>TBSE-025</b>	1	25	36	120	8

### Marine Fuel Hose ISO 7840 Type A - TBDE



**Tube:** Black smooth rubber suitable for use with diesel, petrol and unleaded fuels.  
**Reinforcement:** Synthetic textile fabric braid.  
**Cover:** Black smooth abrasion resistant rubber.  
**Temperature Range:** -30°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure		Coil Lengths (m)
	ins	mm		PSI	Bar	
<b>TBDE-006</b>	1/4	6	16	50	3.4	100
<b>TBDE-008</b>	5/16	8	18	50	3.4	100
<b>TBDE-010</b>	3/8	10	20	50	3.4	100
<b>TBDE-013</b>	1/2	12	23	50	3.4	100
<b>TBDE-016</b>	5/8	16	26.5	50	3.4	100
<b>TBDE-019</b>	3/4	19	30	50	3.4	100
<b>TBDE-025</b>	1	25	36	50	3.4	40
<b>TBDE-032</b>	1 1/4	32	43	50	3.4	40
<b>TBDE-038</b>	1 1/2	38	49	50	3.4	40
<b>TBDE-051</b>	2	51	62	50	3.4	40

### Car Heater Hose SAE 20R3c (212) - ICAR



**Tube:** Black smooth EPDM rubber resistant to glycol based anti-freeze solutions.  
**Reinforcement:** Polyester cord reinforcement.  
**Cover:** Black smooth abrasion resistant rubber.  
**Temperature Range:** -30°C to + 100°C.

Part Number	Bore Size		O.D. (mm)	Working Pressure		Coil Lengths (m)
	ins	mm		PSI	Bar	
<b>ICAR-010</b>	3/8	10	20	130	9	100
<b>ICAR-012</b>	1/2	12	21	130	9	100
<b>ICAR-016</b>	5/8	16	25	130	9	100
<b>ICAR-019</b>	3/4	19	29	130	9	50
<b>ICAR-025</b>	1	25	33	130	9	50

## RUBBER HOSE

Fuel Hose Dispenser



Part Number

**FHD-01**

Swage Ferrule for Industrial - PVC Hose Light Duty Brass



Part Number	I.D. (mm)	O.D. (mm)	Hole Diameter
<b>BR/LDF-06-12</b>	12	14	6
<b>BR/LDF-06-13</b>	13	15	6
<b>BR/LDF-06-15</b>	15	17	6
<b>BR/LDF-08-15</b>	15	17	8
<b>BR/LDF-10-17</b>	17	19	10
<b>BR/LDF-12-18</b>	18	20	12
<b>BR/LDF-12-20</b>	20	22	12
<b>BR/LDF-15-23</b>	23	25	15
<b>BR/LDF-15-25</b>	25	27	15
<b>BR/LDF-18-28</b>	28	30	18
<b>BR/LDF-20-30</b>	30	32	20
<b>BR/LDF-20-33</b>	33	35	20
<b>BR/LDF-25-36</b>	36	38	25
<b>BR/LDF-25-40</b>	40	42	25

3.  
1

Swage Ferrule for Industrial and PVC Hose - Light Duty Steel



Part Number	I.D. (mm)	O.D. (mm)	Hole Diameter
<b>LDF-06-12</b>	12	14	6
<b>LDF-06-13</b>	13	15	6
<b>LDF-06-15</b>	15	17	6
<b>LDF-08-15</b>	15	17	8
<b>LDF-10-17</b>	17	19	10
<b>LDF-12-18</b>	18	20	12
<b>LDF-12-20</b>	20	22	12
<b>LDF-15-23</b>	23	25	15
<b>LDF-15-25</b>	25	27	15
<b>LDF-18-28</b>	28	30	18
<b>LDF-20-30</b>	30	32	20
<b>LDF-20-33</b>	33	35	20
<b>LDF-25-36</b>	36	38	25
<b>LDF-25-40</b>	40	42	25
<b>LDF-36-46</b>	46	50	36
<b>LDF-40-57</b>	57	60	40
<b>LDF-52-67</b>	67	70	52
<b>LDF-63-76</b>	76	80	63
<b>LDF-71-86</b>	86	90	71

Swage Ferrule for Industrial - PVC Hose Light Duty Aluminium



Part Number	I.D. (mm)	O.D. (mm)	Hole Diameter
<b>AL/LDF-06-12</b>	12	14	6
<b>AL/LDF-06-13</b>	13	15	6
<b>AL/LDF-06-15</b>	15	17	6
<b>AL/LDF-08-15</b>	15	17	8
<b>AL/LDF-10-17</b>	17	19	10
<b>AL/LDF-12-18</b>	18	20	12
<b>AL/LDF-12-20</b>	20	22	12
<b>AL/LDF-15-23</b>	23	25	15
<b>AL/LDF-15-25</b>	25	27	15
<b>AL/LDF-18-28</b>	28	30	18
<b>AL/LDF-20-30</b>	30	32	20
<b>AL/LDF-20-33</b>	33	35	20
<b>AL/LDF-25-36</b>	36	38	25
<b>AL/LDF-25-40</b>	40	42	25
<b>AL/LDF-36-46</b>	46	50	36
<b>AL/LDF-40-57</b>	57	60	40
<b>AL/LDF-52-67</b>	67	70	52
<b>AL/LDF-63-76</b>	76	80	63
<b>AL/LDF-71-86</b>	86	90	71

### Swage Ferrule for Industrial and PVC Hose - Light Duty Stainless Steel



Part Number	I.D. mm	O.D. mm	Hole Diameter
<b>SS/LDF-06-12</b>	12	14	6
<b>SS/LDF-06-13</b>	13	15	6
<b>SS/LDF-06-15</b>	15	17	6
<b>SS/LDF-08-15</b>	15	17	8
<b>SS/LDF-10-17</b>	17	19	10
<b>SS/LDF-12-18</b>	18	20	12
<b>SS/LDF-12-20</b>	20	22	12
<b>SS/LDF-15-23</b>	23	25	15
<b>SS/LDF-15-25</b>	25	27	15
<b>SS/LDF-18-28</b>	28	30	18
<b>SS/LDF-20-30</b>	30	32	20
<b>SS/LDF-20-33</b>	33	35	20
<b>SS/LDF-25-36</b>	36	38	25
<b>SS/LDF-25-40</b>	40	42	25

### Propane Gas Hose EN559/BS3212 - GS/IPR020



**Tube:** Black LPG-resistant smooth NBR rubber  
**Reinforcement:** High strength polyester 2 ply yarn  
**Cover:** Galvanised Steel overbraided weather, abrasion ozone and flame resistant orange compound  
**Coil Lengths:** 30 up to 100 metres.  
**Temperature Range:** -35°C to +80°C

Part Number	ins	Bore Size mm	O.D. (mm)	Working Pressure PS	Working Pressure Bar
<b>GS/IPR020-006</b>	1/4	6.3	13.3	290	20
<b>GS/IPR020-008</b>	5/16	8.0	15.0	290	20
<b>GS/IPR020-010</b>	3/8	10.0	17.0	290	20

### Propane Gas Hose EN559/BS 3212 - WR/IPR020



**Tube:** Black LPG resistant smooth NBR rubber  
**Reinforcement:** Steel Braided wire  
**Cover:** Weather, abrasion ozone and flame resistant orange compound  
**Coil Lengths:** 30 up to 100 metres.  
**Temperature Range:**

Part Number	ins	Bore Size mm	O.D. mm	Working Pressure PSI	Working Pressure Bar
<b>WR/IPR020-006</b>	1/4	6.3	14.0	290	20
<b>WR/IPR020-008</b>	5/16	8.0	16.0	290	20
<b>WR/IPR020-010</b>	3/8	10.0	18.0	290	20
<b>WR/IPR020-012</b>	1/2	12.5	21.0	290	20

### Fuel Hose Stainless Steel Overbraided - SS/PVZA



**Tube:** Nitrile Rubber  
**Reinforcement:** Unreinforced  
**Cover:** 304 Stainless Steel Overbraid  
**Coil Lengths:** 50 metres  
**Temperature Range:** -20°C to +80°C

Part Number	Size	Bore Size ins	Bore Size mm	O.D. mm	Working Pressure PSI	Working Pressure Bar
<b>SS/PVZA-006</b>	04	1/4	6.0	10.0	217	15
<b>SS/PVZA-008</b>	05	5/16	8.0	12.0	217	15
<b>SS/PVZA-010</b>	06	3/8	10.0	14.0	217	15
<b>SS/PVZA-012</b>	08	1/2	12.0	17.0	217	15
<b>SS/PVZA-016</b>	10	5/8	16.0	22.0	217	15
<b>SS/PVZA-019</b>	12	3/4	19.0	27.0	145	10
<b>SS/PVZA-025</b>	16	1	26.0	34.0	145	10
<b>SS/PVZA-032</b>	20	1 1/4	32.0	44.0	145	10
<b>SS/PVZA-038</b>	24	1 1/2	38.0	54.0	87	6
<b>SS/PVZA-050</b>	32	2	50.0	64.0	87	6

### Fuel Hose Galvanised Steel Overbraided - GSPVZA



**Tube:** Nitrile Rubber  
**Reinforcement:** Unreinforced  
**Cover:** Galvanised Steel Overbraid  
**Coil Lengths:** 50 metres  
**Temperature Range:** -20°C to +80°C

Part Number	Size	Bore Size ins	Bore Size mm	O.D. mm	Working Pressure PSI	Working Pressure Bar
<b>GS/PVZA-006</b>	04	1/4	6.0	10.0	217	15
<b>GS/PVZA-008</b>	05	5/16	8.0	13.0	217	15
<b>GS/PVZA-010</b>	06	3/8	10.0	15.0	217	15
<b>GS/PVZA-012</b>	08	1/2	12.0	19.0	217	15
<b>GS/PVZA-016</b>	10	5/8	16.0	21.0	217	15
<b>GS/PVZA-019</b>	12	3/4	19.0	25.0	145	10
<b>GS/PVZA-025</b>	16	1	25.0	32.0	145	10
<b>GS/PVZA-032</b>	20	1 1/4	32.0	44.0	145	10
<b>GS/PVZA-038</b>	24	1 1/2	38.0	54.0	87	6
<b>GS/PVZA-050</b>	32	2	50.0	64.0	87	6